



TOP1 FORKLIFT MANUFACTURER AND SALER
IN CHINA FOR CONSECUTIVE 24 YEARS

CBD20/25/28/30

Electric Ride-on Pallet Truck

Advantages

Configuration and Performance

- ⊙ Electronic power steering system, light and low noise.
- ⊙ Drive unit floating bodies with patent design.
- ⊙ AC Driving system, No carbon brush, maintenance free.
- ⊙ USA CURTIS driving controller.
- ⊙ Electromagnetic, regenerative braking system.
- ⊙ Automatic lifting limit, extend the life of the battery and motor.

Safety

- ⊙ Curve automatic deceleration devices, more safe.
- ⊙ Stepless speed control system, safe and quiet.
- ⊙ Controller with Multiple automatic protection.
- ⊙ Emergency reversing device/Emergency brake switch.



EPS | AC

Steering automatic deceleration

Customized Wide Legs

⊙ The difference between CBD30-470 and CBD30-460

Model	Load capacity (kg)	Battery capacity (Ah)		Overall fork width (mm)	Battery installation
		Standard	OPTION		
CBD30-470	2000-3000	280	360	540/600/650/685/1070	Hoisting
CBD30-460	2000-3000	270	210	550/600/650/685	Side-loaded battery

Feature		
Model		CBD20/25/28/30
Configuration No.		470
Loading capacity	kg	2000/2500/2800/3000
Load center	mm	600
Wheel base	mm	1480
Operating type		Stand On
Wheels		
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/2/4
Driving wheel size	mm	Ø248×75
Bearing wheel size	mm	Ø84×80(Double wheels)
Balance wheel size	mm	Ø115×55
Dimension		
Min.fork lowered height	mm	85
Max.fork lifting height	mm	205
Max.lifting height	mm	120
Overall fork width	mm	540/600/650/685
Inside width between forks	mm	200/260/310/345
Fork length	mm	1150/1200
Fork width	mm	170
Fork thickness	mm	75
Overall length	mm	1920/2335
Overall width	mm	720
Overall height(With handle)	mm	1455
Overall height(Without handle)	mm	900
Min.Turning radius	mm	1735/2140
Min.Aisle width for pallets 800×1200	mm	2060/2451
Min.Aisle width for pallets 1000×1200	mm	2090/2468
Performance		
Travel speed,laden/unladen	km/h	6/6
Lift speed,laden/unladen	mm/s	56/60
Lowering speed,laden/unladen	mm/s	57/59
Gradeability,laden/unladen	%	5/7
Electrical configuration		
Drive motor	kW	AC 1.5
Lift motor	kW	DC 1.2
Steering motor	kW	DC 0.15
Battery voltage / capacity	V/Ah	24/280
Brake		Electromagnetic/Regenerative
Controller		CURTIS
Weight		
Battery weight	kg	250
Service weight with battery	kg	848

* Details of specifications and equipment are based on information available at time of printing and may change without notice.

ÖZİSMAK



ÖZİSMAK İSTİF MAKİNELERİ SANAYİ ve TİC. LTD. ŞTİ.

Merkez Adres : İkitelli O.S.B. Dolapdere San. Sit. 25. Ada No:14 Başakşehir/İstanbul
 Telefon : +90 (212) 671 50 24 pbx Fax : +90 (212) 671 49 82
 Fabrika Adres : Türkgücü Mah. Türkgücü O.S.B. Yılmaz Alpaslan Cad. No:64 Çorlu/Tekirdağ
 Telefon : +90 (282) 681 80 77 pbx E-mail : info@ozismak.com www.ozismak.com