

# CDD10-070

## 1.0 Ton Electric Fork Over Stacker

Lifting Height: 2000-3300mm

### Load Curve



### Advantages

#### Configuration and Performance

- Separately excited motor, Strong climbing ability.
- High strength forks.
- Built-in charger.
- Automatic lifting limit, Motor and battery life extension.

#### Safety

- Stepless speed control system, safe and quiet.
- Controller with Multiple automatic protection
- Emergency reversing device/Emergency brake switch.



TOP1 FORKLIFT MANUFACTURER AND SALER  
IN CHINA FOR CONSECUTIVE 24 YEARS

**Built-in charger**

**Free-maintained battery**

**Integrated fork, much stronger**

| Type      | Lift height (mm)    | Mast type        | Outside width between legs (mm) | Inside width between legs (mm) |
|-----------|---------------------|------------------|---------------------------------|--------------------------------|
| CDD10-070 | 2000/2500/3000/3300 | Standard 2-STAGE | 550/600/650/685                 | 180/230/280/315                |

| Feature                                                  |      |                              |
|----------------------------------------------------------|------|------------------------------|
| Model                                                    |      | CDD10                        |
| Configuration No.                                        |      | 070                          |
| Type                                                     |      | Fork over                    |
| Mast type                                                |      | Standard 2-Stage             |
| Load capacity                                            | kg   | 1000                         |
| Load center                                              | mm   | 600                          |
| Wheel base                                               | mm   | 1150                         |
| Operating type                                           |      | Walkie                       |
| Wheels                                                   |      |                              |
| Wheels type                                              |      | PU                           |
| Wheel quantity Driving wheel/Balance wheel/Bearing wheel |      | 1/1/4                        |
| Dimension                                                |      |                              |
| Standard lift height                                     | mm   | 2000/2500/3000/3300          |
| Max.extend height                                        | mm   | 2385/2885/3385/3685          |
| Mast lowered height                                      | mm   | 1550/1800/2050/2200          |
| Lowered fork height                                      | mm   | 90                           |
| Fork size(length/width/thickness)                        | mm   | 1150(1220)/185/55            |
| Overall length                                           | mm   | 1733                         |
| Overall width                                            | mm   | 790                          |
| Outside width between forks                              | mm   | 550/600/650/685              |
| Inside width between forks                               | mm   | 180/230/280/315              |
| Min.Turning radius                                       | mm   | 1350                         |
| Min.Aisle width for pallets 800×1200                     | mm   | 1914                         |
| Min.Aisle width for pallets 1000×1200                    | mm   | 1955                         |
| Min.ground clearance                                     | mm   | 30                           |
| Performance                                              |      |                              |
| Travel speed,laden/unladed                               | km/h | 3/3.5                        |
| Lift speed,laden/unladed                                 | mm/s | 130/230                      |
| Lowering speed,laden/unladed                             | mm/s | 130/230                      |
| Gradeability,laden/unladed                               | %    | 5/7                          |
| Electrical configuration                                 |      |                              |
| Drive motor/Lift motor/Steering motor                    | kW   | DC0.63/DC2.0                 |
| Battery voltage                                          | V    | 24                           |
| Battery capacity                                         | Ah   | 70                           |
| Brake                                                    |      | Electromagnetic/Regenerative |
| Controller                                               |      | HELI(Options CURTIS)         |
| Weight                                                   |      |                              |
| Battery weight                                           | kg   | 48                           |
| Service weight with battery                              | kg   | 580                          |

\* Details of specifications and equipment are based on information available at time of printing and may change without notice.

**ÖZİSMAK**



**ÖZİSMAK İSTİF MAKİNELERİ SANAYİ ve TİC. LTD. ŞTİ.**

Merkez Adres : İkitelli O.S.B. Dolapdere San. Sit. 25. Ada No:14 Başakşehir/İstanbul  
 Telefon : +90 (212) 671 50 24 pbx Fax : +90 (212) 671 49 82  
 Fabrika Adres : Türkgücü Mah. Türkgücü O.S.B. Yılmaz Alpaslan Cad. No:64 Çorlu/Tekirdağ  
 Telefon : +90 (282) 681 80 77 pbx E-mail : info@ozismak.com www.ozismak.com