


CPD16

1.6 Ton Counterbalanced Electric Stacker

LIFTING HEIGHT: 1400-4500MM

Load Curve



Advantages

Configuration and Performance

- Electronic power steering system, light and low noise.
- Two-way magnetic valve, three drop speed mode.
- AC Driving system, No carbon brush, maintenance free.
- USA CURTIS driving controller.
- Electromagnetic, regenerative braking system.
- Automatic lifting limit, proximity switch, long life.

Safety

- Curve automatic deceleration devices, more safe.
- Vehicle decelerates automatically at higher position.
- Stepless speed control system, safe and quiet.
- Controller with Multiple automatic protection.
- Emergency reversing device/Emergency brake switch.
- High position automatic reduction device.

AC | EPS

Options fork tilt device

Counter-balanced electric stacker



Type	Lift height (mm)	Mast type	Option
CPD16-D970	1400/2000/2500/3000/3300/3600/4000	Standard 2-STAGE	TILTING DEVICE
CPD16-970	3700/3900/4200/4500	FULL FREE 3-STAGE	TILTING DEVICE

Feature				
Model		CPD16-D970		CPD16-970
Type		Counterbalanced		
Mast type		Standard 2-Stage		Full free 3-Stage
Load capacity	kg	1600		1600
Load center	mm	500		500
Wheel base	mm	1529		1529
Operating type		Walkie/Stand On		
Wheels				
Wheels type		PU		PU
Wheel quantity Driving wheel/ Balance wheel/Bearing wheel		1/0/2		1/0/2
Dimension				
Standard lift height	mm	1400/2000/2500/3000/ 3300/3400/4000		3700/3900/4200/4500
Lowered fork height	mm	55		55
Fork size(length/width/thickness)	mm	1070/100/40		1070/100/40
Overall length	mm	2942/3362		2942/3362
Overall width	mm	1015		1015
Max.extend height	mm	2400/3000/3500/4000 /4300/4600/5000		4350/4550/4650/5150
Mast lowered height	mm	1230/1580/1780/2030 /2130/2330/2545		1817/1917/2002/2102
Min.Turning radius	mm	1808/2200		1808/2200
Min.Aisle width for pallets 800×1200	mm	3140/3520		3140/3520
Min.Aisle width for pallets 1000×1200	mm	3160/3538		3160/3538
Min.ground clearance	mm	80		80
Performance				
Travel speed,laden/unladen	km/h	5/5		5/5
Lift speed,laden/unladen	mm/s	130/180		130/180
Lowering speed,laden/unladen	mm/s	100/230		100/230
Gradeability,laden/unladen	%	5/7		5/7
Electrical configuration				
Drive motor/Lift motor/Steering motor	kW	AC1.5/DC3/DC0.15		AC1.5/DC3/DC0.15
Battery voltage	V	24		24
Battery capacity	Ah	270		270
Brake		Electromagnetic/Regenerative		
Controller		CURTIS		
Weight				
Battery weight	kg	245		245
Service weight with battery	kg	1900		2010

* Details of specifications and equipment are based on information available at time of printing and may change without notice.

