


CTD10-050

1.0 Ton Electric Straddle Stacker

Lifting Height: 2000-3300mm

Load Curve



Advantages


Configuration and Performance

- O Separately excited motor, Strong climbing ability.
- O High strength forks.
- O Built-in charger.
- Automatic lifting limit, Motor and battery life extension.

Safety

- O Stepless speed control system, safe and quiet.
- O Controller with Multiple automatic protection
- Emergency reversing device/Emergency brake switch.





Built-in charger

Free-maintained battery


Adjustable forks at three choices


Туре	Lift height (mm)	Mast type	Outside width between legs (mm)	Inside width between legs (mm)
CTD10-050	2000/2500/3000/3300	Standard 2-STAGE	1120/1270/1420	970/1120/1270

CTD10-050

Feature		
Model		CTD10-050
Туре		Straddle
Mast type		Standard 2-Stage
Load capacity	kg	1000
Load center	mm	600
Wheel base	mm	1204
Operating type		Walkie
Wheels	Ju ni	· · · · · · · · · · · · · · · · · · ·
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/1/2
Dimension		
Standard lift height	mm	2000/2500/3000/3300
Max.extend height	mm	2593/3093/3593/3893
Mast lowered height	mm	1620/1870/2120/2270
Lowered fork height	mm	55
Fork size(length/width/thickness)	mm	1070/100/40
Overall length	mm	1721
Overall width	mm	940
Outside width between forks	mm	200-812
Inside width between forks	mm	0-612
Min.Turning radius	mm	1411
Min.Aisle width for pallets 800×1200	mm	1970
Min Aisle width for pallets 1000×1200	mm	2010
MIn.ground clearance	mm	50
Performance	V	
Travel speed, laden/unladed	km/h	3/3.5
Lift speed, laden/unladed	mm/s	120/180
Lowering speed, laden/unladed	mm/s	120/120
Gradeability, laden/unladed	%	5/7
Electrical configuration		
Drive motor/Lift motor/Steering motor	kW	DC0.63/DC2.0
Battery voltage	V	24
Battery capacity	Ah	85
Brake		Electromagnetic/Regenerative
Controller	10 10	HELI(Options CURTIS)
Weight		· ·
Battery weight	kg	48
Service weight with battery	kg	710

^{*} Details of specifications and equipment are based on information available at time of printing and may change without notice.







ÖZİSMAK İSTİF MAKİNELERİ SANAYİ ve TİC. LTD. ŞTİ.

Merkez Adres : İkitelli O.S.B. Dolapdere San. Sit. 25. Ada No:14 Başakşehir/İstanbul

Telefon: +90 (212) 671 50 24 pbx Fax: +90 (212) 671 49 82
Fabrika Adres: Türkgücü Mah. Türkgücü O.S.B. Yılmaz Alpaslan Cad. No:64 Çorlu/Tekirdağ

Telefon: +90 (282) 681 80 77 pbx E-mail: info@ozismak.com www.ozismak.com